

Why Water Is Seeping Through Your Garage Door

Water leaking under a garage door is usually caused by a breakdown in the seal between the door and the floor, but the source may also be above on the opening. An overhead garage door must close evenly against the garage door frame, garage floor, and garage door threshold. If any of these surfaces are damaged, uneven, or inadequately sealed, rain can get into the garage.

The bottom weather seal is one of the most critical parts of a water-resistant garage door. This flexible strip presses against the floor when the door closes. Over time, it can become brittle, split, flattened, or pulled out of its retainer. A damaged garage door panel can also allow water to pass through openings, dents, separating joints, or damaged seams.



Water may get in at several locations:

- Under the door through a deteriorated bottom weather seal
- At the sides through spaces between the door and garage door frame
- Between panels through damaged joints or bent sections
- Across the garage door threshold where the concrete floor is irregular
- Above the opening if flashing, trim, or caulking has deteriorated

Finding the exact entry point is important. Replacing a seal will not resolve the problem if water is actually coming through a cracked panel, a leaking garage door frame, or drainage moving [Gate Repair Services in Los Angeles](#) toward the opening.

Frequent Causes of Garage Door Water Leaks in Los Angeles

Los Angeles County has a coastal Mediterranean climate with extended dry spells followed by wintertime seasonal rainfall. Those months of bright sun and warmth can cause rubber seals and caulking to dry out or crack before the first major storm reveals a problem. During intense winter rain, even a small opening can allow substantial rainwater into a garage.

Wind-driven rain is especially problematic in Santa Monica, Venice, Long Beach, and other coastal communities. Strong gusts can force water beneath the door, through side gaps, and into small cracks around the garage door frame. Coastal exposure may also speed up deterioration of metal hardware, fasteners, and weather seals.

A sloped driveway is another regular source of problems. Driveways are often designed to move water away from a home, but settlement, resurfacing, or poor grading can create a low point at the garage entrance. Water then gathers at the door instead of draining away. A standard seal may not stop water that is flowing directly toward the opening with force.

Older homes in Northeast Los Angeles, South Los Angeles, and the San Fernando Valley may have worn garage doors, frames, concrete floors, or drainage systems. A door installed decades ago may no longer sit level, while the surrounding frame may have shifted or developed gaps. In these cases, garage door repair may need to be coordinated with threshold, frame, or drainage work.

Damaged Weatherstripping and Bottom Seals

Weatherstripping protects the edges and moving joints of a garage door. The garage door seal at the bottom is commonly made from flexible rubber or vinyl and slides into a channel along the lowest panel. A rubber gasket may become hard, cracked, torn, or permanently compressed after years of exposure.

When the seal no longer touches the floor across its full width, water can enter beneath the door. Homeowners often describe this as rain coming into the garage or water leaking under garage door panels. Gaps are particularly common at the corners, where the floor may be slightly lower than the central area.

A correctly installed seal acts as a water barrier, but it should not be relied upon to correct an extremely uneven floor. If the concrete slopes toward the garage, a garage door threshold seal can provide an extra raised barrier. The threshold must be attached to a dry, clean surface and positioned so the door closes firmly without too much pressure.

Inspect the weatherstripping along the sides and top as well. If it is slack, shriveled, or separated from the garage door frame, rain can enter even when the bottom seal is in good condition. A fully weatherproof weatherproof garage door may require replacement of the bottom seal, side stops, top seal, and worn caulking.

Cracked Panels, Misalignment, and Door Gaps

A deteriorated garage door panel can allow water through cracks, holes, dents, or broken joints. Wood panels may absorb moisture and swell, while older steel panels can rust around fasteners and seams. Insulated panels may separate internally after impact or long-term exposure to moisture.

Door alignment is also important. If the sections do not meet properly, one side may have a large gap against the floor or frame. Misalignment can result from damaged rollers, loose hinges, bent garage door tracks, broken cables, or a door that has shifted in its opening. A garage door inspection should evaluate movement and spacing rather than focusing only on visible holes.

Panel replacement may be suitable when one section has isolated damage and matching parts remain available. However, replacing one panel on an older door can create differences in color, design, weight, or insulation. If several sections are damaged or the structure is badly warped, full garage door replacement may be more practical.

How to Check a Leaking Garage Door Safely

Start with a careful examination during daylight and after rainfall if possible. Keep the door fully closed and look for daylight beneath or beside it. Check for wet tracks, water marks, peeling paint, swollen wood, rust, mold, and damp items stored near the opening. Following the highest wet point can help distinguish water intrusion from condensation or a plumbing leak.

For garage door safety, do not remove springs, cables, drums, hinges, or track hardware. Springs and cables hold significant tension, and a sudden release can cause severe injury. A torsion spring above the door is particularly dangerous to adjust without the correct tools and training.

With the door closed, check the bottom weather seal for cracks, flattening, missing sections, and gaps. Inspect the threshold and concrete for cracks or low areas. Examine the garage door frame for deteriorated trim and failed caulking. If the door is safe to operate, watch it open and close from a distance. Discontinue use if it binds, falls, makes grinding sounds, or moves unevenly.

Photograph water damage with photographs and note where water appears after different types of weather. This information helps a technician identify whether the problem is a seal, panel, frame, drainage, or alignment issue.

Garage door repair solutions for water intrusion

The right repair depends on the entry point. Replacing the bottom seal is often the most straightforward solution when the seal is split or worn but the door and floor remain sound. The old strip is removed, the retainer is cleaned, and a correctly sized garage door bottom seal is installed across the door.

If water moves toward the opening, a threshold seal may be added on the garage floor. This creates a raised channel that pairs with the door's bottom seal. The floor must be dry and structurally suitable, and the threshold should not interfere with vehicles, walking paths, or the operation of the door.

Garage door panel repair may involve changing a damaged section, strengthening a minor defect, or correcting a separated joint. Severe warping, rust, or impact damage usually necessitates panel replacement rather than cosmetic patching. Caulking can close stationary gaps around the garage door frame, but it should not be used to seal moving joints or cover active structural problems.

Other repairs may include adjusting garage door alignment, replacing rollers, adjusting tracks, repairing hinges, or improving the frame. If water is collecting because of the driveway or surrounding drainage, a garage door company may identify the issue, but concrete grading, drains, or waterproofing may require a separate licensed contractor.

When to Fix or Replace a Garage Door Panel

Repair a garage door panel when the damage is small, localized, and the section remains structurally sound. Replacement is more appropriate when the panel is separated, badly dented, rusted through, swollen, or no longer aligns with adjacent sections. A damaged panel can continue to admit water and may place extra stress on rollers and tracks.

Consider the age and condition of the complete door. If the existing door is past its prime, poorly insulated, or has repeated failures, an insulated garage door can enhance durability and help moderate temperatures inside the garage. Matching a replacement panel may be difficult for discontinued models, making a new door more attractive.

Garage door replacement cost depends on the construction material, dimensions, insulation level, design, fittings, disposal, and installation. A budget-friendly panel repair may be practical for a newer door, while extensive panel

damage on an aged door can make replacement a better long-term value. Request a written garage door repair estimate that explains both options.

Garage door repair Cost and Pricing in Los Angeles

Garage door repair cost in Los Angeles differs according to the cause, door size, part availability, urgency, and access to the damaged area. A standard seal replacement is generally less expensive than panel replacement, track correction, spring work, or a complete new door. Coastal exposure, unusual door designs, and older construction can also influence the work required.

Garage door repair pricing should clearly break down labor, parts, disposal, permit-related charges if applicable, and any service call fee. A technician may charge a service call fee for diagnosis, particularly outside normal business hours. Ask whether that fee is applied toward approved repair work.

Do not select a provider solely because it advertises the lowest price. A proper inspection should explain why water is entering and whether the proposed repair will address the actual source. The cheapest new seal will not solve a sloped driveway or a structurally damaged panel.

Typical Costs for Springs, Panels, Seals, and Openers

Homeowners searching for garage door spring replacement near me should understand that spring work is distinct from a water-leak repair. The garage door spring cost depends on the spring type, door weight, number of springs, and labor. Torsion spring repair should be performed by a trained technician because the spring stores substantial energy.

Seal replacement is usually simpler, while panel work costs more because the technician may need to match the section, remove hardware, balance the door, and test the opener. If the garage door opener is damaged by moisture or must be upgraded, the garage door opener installation cost includes the unit, mounting, programming, safety reversal testing, and labor.

Garage door replacement cost includes the door itself, tracks or other hardware when needed, installation, removal of the old door, and optional accessories. Ask for a detailed estimate rather than relying on a broad advertised range. This is especially important when comparing panel repair with full replacement.

EM Garage Doors And Gate Service Inc

19629 Cantara St, Reseda, CA 91335

(818) 919-0785

<https://emgaragedoorsandgateservice.com/>

<https://maps.app.goo.gl/XujLWxA4pAQKARQT8>

34.2193569, -118.5613022

Two Car Garage Door Replacement Cost Considerations

The 2 car garage door replacement cost is usually greater than replacing a single-car door because the door is wider, more substantial, and may require stronger hardware and more installation labor. A two car garage door replacement cost also depends on whether the opening uses one double garage door or two separate doors.

A double garage door has a large continuous span, so damage, wind exposure, and alignment can affect the complete system. Insulation, window sections, custom finishes, smart controls, and reinforced tracks add to the price. Installation labor may increase when the frame needs adjustment or the old structure has water damage.

Compare the full proposal, including measurements, hardware, opener compatibility, weather seals, threshold work, removal, warranty terms, and labor. The lowest door price may not indicate the lowest total project cost.

Homeowner Fixes Compared With Professional Garage Door Repair

A few homeowners can complete a DIY weather seal replacement if the door is secure, the correct replacement seal is available, and the retainer is undamaged. Leave the opener disconnected only according to the manufacturer's instructions, work with the door secured, and do not force a stuck seal or remove tensioned components.

Call a professional garage door technician for damaged panels, severe gaps, bent tracks, loose cables, unusual noises, or a door that is heavy or uneven. A professional can test balance, alignment, rollers, hinges, safety sensors, and the opener while diagnosing the leak.

Never attempt torsion spring repair, cable replacement, or major track adjustment as a casual DIY project. Incorrect work can make the door to fall or release stored energy. Emergency garage door repair is appropriate when the door is left open, has fallen off its tracks, is blocking a vehicle, or presents an immediate safety risk.

How to Find Garage Door Repair Near Me in Los Angeles

When searching for garage door repair near me, look for a local company that specifically handles leak diagnosis, weather seals, panels, frames, and drainage-related concerns. Confirm that the provider serves your part of Los Angeles and offers a clearly defined local service area. Same-day repair may be available for urgent problems, but water sealing work still requires a thorough inspection.

Choose a licensed garage door contractor and verify licensing through the California Contractors State License Board. Ask for proof of insurance, business identification, warranty terms, and references where appropriate. A licensed garage door technician should explain whether the repair involves the door, frame, threshold, driveway, or another building component.

Before approving work, request a written repair estimate listing labor, parts, taxes, service fees, and any after-hours charges. Ask whether the quote covers testing the door after repair and whether additional damage will require authorization. These steps help Los Angeles homeowners avoid unclear garage door repair pricing.

How to Prevent Future Garage Door Water Leaks

Regular garage door maintenance helps prevent water intrusion and identifies small defects before they become expensive repairs. At least once a year, inspect the bottom seal, side weatherstripping, threshold, frame, panels, hinges, rollers, and tracks. After major winter storms, examine for new gaps, water marks, or movement in the door.

Maintain the garage door tracks clear and have moving hardware serviced according to the manufacturer's recommendations. Do not apply random lubricant to the bottom seal or paint over flexible weatherstripping. Change cracked seals with materials approved for outdoor exposure and the local climate.

Maintain drainage around the garage whenever possible. Clean leaves from drains, keep downspouts directed away from the opening, and address settled concrete or standing water. A threshold can help prevent water intrusion, but it cannot replace proper grading when runoff is substantial.

Weatherproof materials, intact caulking, corrosion-resistant hardware, and an annual inspection can extend the life of the door. In Southern California, the best time to check seals is before the rainy season, not after the first

storm exposes a leak.

Common Questions About Garage Door Water Leaks

What can I do to stop water from leaking under my garage door?

Examine the bottom weather seal, garage door threshold, floor grading, and side weatherstripping. If the seal is damaged or compressed, install new garage door seal components with the proper size. A garage door threshold seal may assist when water flows across an uneven floor. If the door is out of alignment or the driveway slopes toward the garage, have a professional complete a water leak diagnosis before choosing a repair.

How much does garage door repair in Los Angeles?

Garage door repair cost is determined by whether the problem involves a seal, panel, track, spring, opener, frame, or drainage issue. Garage door repair pricing can also involve a service call fee, labor, parts, and emergency scheduling. Ask for a written garage door repair estimate with each charge clearly itemized, and compare the cost of repair with the likely garage door replacement cost when damage is widespread.

Is it better to replace a leaking garage door seal or the entire door?

Change the weather seal when the door is still structurally intact and the leak is confined to the bottom or edges. Consider a new garage door when more than one panel is damaged, the frame is severely damaged, the door is continually misaligned, or replacement parts are unavailable. An inspection can establish whether a seal is the true source of the barrier failure or only one symptom of a more serious issue.

Can a damaged garage door panel lead to water leaks?

That's correct. A deteriorated garage door panel can have cracks, holes, bent joints, rust, or gaps that allow rainwater to enter. Panel damage can also impact door alignment and prevent the bottom seal from contacting the floor evenly. Depending on the severity and age of the door, the appropriate solution may be panel repair, panel replacement, or complete replacement.

How do I find dependable garage door repair near me in Los Angeles?

Look for an established local provider, confirm its license through the California Contractors State License Board, and ensure insurance and service coverage in your community. Choose a licensed garage door technician who performs a garage door inspection and provides a written estimate for labor, parts, and fees. Ask specifically about urgent garage door service, warranty coverage, and expertise with water leaks, older homes, and coastal conditions.